

Project	Type
Product Code	Date

# VALTO LS 400E/600: €40

## Europe/Asia/Australia

### Summary

- Hybrid design allows for operation with line voltage 100-277 VAC and HID magnetic ballast
- Five years or 50,000 hours warranty<sup>3</sup>

### 150W Version - Open or Vented Fixture

- 20,000 Lumens, 130 L/W
- Ambient air operation to 50°C/122°F at full power

### 105W Version - Enclosed or IC Fixture


- 15,000 Lumens, 143 L/W
- Ambient air operation at full output power:
  - 45°C/122°F for enclosed or IC fixture
  - 65°C/149°F for vented fixture or open

### Control Options

- 0-10V (dim to off at 0V)
- RF occupancy and daylight sensor option
- Bluetooth option

### Mechanical

- E40 socket compatible
- Vertical orientation only
- Beautiful anodized solid aluminum body
- 1.65 kg/3.6 lb
- Fanless for high reliability and efficiency
- Safety harness optional



### Photometry

- No external reflector needed thus no reflector loss factor
- 50° glare cutoff with  $UGR_{ave} < 15$
- Optical distribution with high uniformity  $E_{Min/Avg} > 0.75$  SC=0.5 to 1.5

### Electrical - Type A

- 90-305 VAC 50/60 Hz input voltage max
- No flicker/6 kV surge protection
- No inrush current
- PF>0.9/THD<20%

VAC	100	110	120	220	240	277
AMPS	1.5	1.36	1.25	0.68	0.63	0.54

### Ballast Compatibility - Type B

VL series is compatible with HID magnetic ballast between 175-600W. Such ballast types include probe start, pulse start, CWA or reactive. The table below shows compatible ballast that have been tested.

	175W	200W	250W	320W	350W	400W	600W
<b>Metal Halide</b>	M57, M137/ M152 MH175		M138/ M153, MH250	M132/ M154	M131	M155/ M135, M59, MH400	
<b>HPS</b>		S66	S50, NG250			S51, NG400	S106, NG600
<b>MV</b>	H175						

### Certifications



### Ordering Information

Controls	Fixture Compatibility	Max. Envir. Temp.	Product Code	Part #	Watts	Lumens	CCT
<b>0-10V</b>	Open or Vented	50°C	00620	VAL-E40-150-8-40-VL-AN-B90-010-000	150	20,000	4,000K
			00628	VAL-E40-150-8-50-VL-AN-B90-010-000	150	20,000	5,000K
	Open or Vented/IC or Enclosed	65°C/45°C <sup>1</sup>	00616	VAL-E40-105-8-40-VL-AN-B90-010-000	105	15,000	4,000K
			00624	VAL-E40-105-8-50-VL-AN-B90-010-000	105	15,000	5,000K
<b>Occupancy and Daylight Sensor</b>	Open or Vented	50°C	03210	VAL-E40-150-8-40-VL-AN-B90-OC1-000	150	20,000	4,000K
			03214	VAL-E40-150-8-50-VL-AN-B90-OC1-000	150	20,000	5,000K
	Open or Vented/IC or Enclosed	65°C/45°C <sup>1</sup>	03208	VAL-E40-105-8-40-VL-AN-B90-OC1-000	105	15,000	4,000K
			03212	VAL-E40-105-8-50-VL-AN-B90-OC1-000	105	15,000	5,000K

1. Unless otherwise specified, all values are typical at 25°C with no optical accessory.  
 2. 65°C for open or vented fixture, 45°C in total enclosed for Enclosed or IC Fixture  
 3. See limited warranty for details.

4. Not intended for use in wet environments or environments containing airborne corrosive agents such as chemicals, solvents or cutting fluids.  
 5. Specifications subject to change without notice